

CLAIMS FOR SPECIES B

I claim:

1. A cleansing apparatus connectable to a whole number of pressurized liquid sources, comprising:
a whole number of tubes for delivering respective liquids from the respective sources to an equal whole number of respective valves;
the valves being controlled by the same whole number of respective actuators;
the valves controlling the flow of the respective liquids into a common header where they are mixed;
the mixed flow passing through a flexible hose to a spray gun;
the spray gun having a spray tip for applying the mixed flow to the body of a user.
19. The apparatus of claim 1, wherein:
the apparatus is mounted on a first surface of a door;
the door being hinged to an enclosure surrounding a space;
the first surface facing inwardly to the space; and
the door hiding at least a portion of the apparatus from view when closed.
20. The apparatus of claim 19, connectable to said whole number of pressurized liquid sources plus one additional pressurized liquid source, further comprising:
one additional tube for delivering an additional liquid from the one additional pressurized liquid source to a flow splitting device;
the flow splitting device creating a bypass stream and a tank input stream;
the tank input stream going to an additive tank;
the additive tank having watertight means for introduction of an additive to the tank;
the tank input stream and the additive mixing together in the tank and creating a tank output stream;

the bypass stream going to a first additional valve being controlled by a first additional actuator;
the tank output stream going to a second additional valve being controlled by a second additional actuator;
the first and second additional valves controlling the flow of the bypass stream and the tank output stream into said common header.

21. The apparatus of claim 20, wherein:
said spray tip is detachable from said spray gun, and is interchangeable with alternative spray tips.
22. The apparatus of claim 21, wherein:
said spray tip comprises means for manual adjustment of spray pattern width and direction.
23. The apparatus of claim 22, wherein:
said actuators and said spray gun are mounted within easy reach from a toilet.
24. The apparatus of claim 23, further comprising said alternative spray tips and user access to said alternative spray tips.

-
9. A cleansing apparatus, comprising:
a faucet comprising first, second, and third inlets;
a first water supply tube feeding a first stream of water to the first inlet of the faucet;
a second water supply tube feeding a second stream of water to a flow splitting means, the splitting means splitting the second stream into a third stream and a fourth stream;
the third stream going to the second inlet of the faucet;
the fourth stream going to an additive tank, and thence to the third inlet of the faucet;

AB
the tank having watertight means for introduction of additive to the tank;
the faucet combining said first, third, and fourth streams into a mixed flow;
the mixed flow going to a spray gun.

25. The apparatus of claim 9, wherein:
the apparatus is mounted on a first surface of a door;
the door being hinged to an enclosure surrounding a space;
the first surface facing inwardly to the space, the door hiding at least a portion of
the apparatus from view when closed.
26. The apparatus of claim 25, wherein:
said fourth stream goes to an additive tank and thence to a first input on a flow
merging means;
said mixed flow going to a second input on the flow merging means;
the flow merging means yielding a merged flow;
the merged flow going to a spray gun.
27. The apparatus of claim 26, wherein:
said flow merging means comprises separate flow controlling means for said first
input and said second input.
28. The apparatus of claim 27, wherein:
said controlling means are actuatable by the fingers of one hand, and said
controlling means and said flow merging means are built into said spray gun;
the spray gun having a spray tip for applying the mixed flow to the body of a user.
29. The apparatus of claim 28, wherein:
said spray tip is detachable from said spray gun, and is interchangeable with
alternative spray tips.
30. The apparatus of claim 29, wherein:

said spray tip comprises means for manual adjustment of spray pattern width and direction.

31. The apparatus of claim 30, wherein:
said actuators and said spray gun are mounted within easy reach from a toilet.
-